

# CLASSIC CRACKMATE

## Polymer Based Crack Filling Powder

### Product:

A factory blended easy-to-use, polymer modified, high strength, non-shrink, cementitious crack filling mortar. Designed for cost effective filling of cracks in concrete, masonry and plaster surfaces including shrinkage cracks in plaster.

### Description:

**Classic Crackmate** is a polymer modified cementitious crack filling mortar with non-shrink properties, prepared by adding the specified quantity of water to the powder. **Classic Crackmate** is used to fill cracks in both interior and exterior concrete, masonry and plaster surfaces. It can also be used as a thin render to even out surfaces.

### Advantages & Benefits:

- Non-Shrink mortar with Strong adhesive properties.
- Excellent crack filling ability.
- Smooth finish.
- Prevent further crack propagation.
- High tensile strength.

### Pack & Coverage:

Available in 0.5 & 1 Kg packs. 1 Kg will fill approx. 30 – 40 m length of cracks cut into 6 mm deep V-groove.

### Instructions for Use:

#### Surface Preparation:

Cut the cracks into 6mm deep V-grooves. Clean the grooves with a brush to remove all loose particles. Sprinkle grooves with clean water.

### Storage Life

**Classic Crackmate** has a shelf life of 6 months when stored, unopened in the original pack, under dry condition at moderate temperatures.

### Mixing:

**Classic Crackmate** should be preferably mixed mechanically using a slow speed drill with paddle attachment, slowly adding 1 Kg of **Classic Crackmate** to 250 to 300 ml of clean water, until a homogenous mortar of smooth, creamy and trowellable consistency is obtained.

### Application:

Fill the prepared cracks tightly with the mortar using a small trowel or putty blade and finish to a level surface. Remove excess mortar with clean moist sponge or soft cloth before it dries totally.

### Handling Precautions:

**Classic Crackmate** is non-toxic, but mildly alkaline when wet. However, in its wet state. If contact with skin occurs, wash well with clean water. Inhalation of dust from the dry material should be avoided.

### Storage Life

**Classic Crackmate** has a shelf life of 6 months when stored, unopened in the original pack, under dry condition at moderate temperatures.

### Variety of Products:

Following are the other similar products from Primadonn Buildtech Pvt. Ltd.

- Classic Coat-RB
- Classic Cure-C
- Classic Epoxy Mortar-301
- Classic Epoxy Patch-302
- Classic Epoxy Primer-273
- Classic Epoxybond-208
- Classic Epoxyseal-204
- Classic ETP-3
- Classic Epoxyseal-204
- Classic ETP-3

# CLASSIC CRACKMATE

Polymer Based Crack Filling Powder

- Classic Epoxyseal-204
- Classic ETP-3
- Classic MA
- Classic Micromate
- Classic Primecoat
- Classic Repmate
- Classic Rust Shield
- Classic Strongcoat-202AR
- Classic TA
- Classic TP
- Classic TT
- Classic Wall Putty



Primadonn Buildtech Pvt. Ltd.

(An ISO 9001:2015 Certified Company)

No: 349, RS Road, Srinivasa Nagar, Kavaraipettai, Gummidipoondi, Chennai-601206.

Phone: +91-9514709240

Mail: support@primadonn.com

[www.primadonn.com](http://www.primadonn.com)