



CLASSIC CRETE TA

High Performance Ceramic Tile Adhesive

Product:

Classic Crete TA can be used in totally submerged conditions. Good open wet time for improved workability.

Uses:

Classic Crete is a high quality adhesive for the permanent fixing of ceramic tiles. It can also be used for fixing of insulation and acoustic boards. Tiled surfaces after curing can be used for damp and submerged services like toilets and swimming pools.

Instructions for Use:

Surface Preparation:

All surfaces must be sound and thoroughly cleaned before **Classic Crete TA** is applied. All traces of grease or oil must be removed with suitable degreaser. All loose particles of mortar and paints must be physically removed.

Mixing:

Classic Crete TA should be mixed with water in the ratio of 3:1 by volume. Water can be reduced or increased slightly to increase required consistency. Powder to be added slowly to the water and not water to powder.

Application:

Classic TA can be applied directly on concrete, cement screeds, cement lime mortars.

Finishing:

Remove excess adhesive with a damp cloth before material has set. Joint grouting may be commenced 24 Hrs. After tiles have been laid, with **Classic Crete TP** joint filler.

Packing:

Available in 25Kg bag.

Coverage:

Classic Crete TA is spread on the substrate to uniform thickness of 3 to 5 mm. Choose work areas so that they can be tiled in adhesive open wet time approximately 30 mins at a 30°C. 25 Kg pack of **Classic Crete TA** covers approximately 4 Sq.mt. at 3 mm thickness.

Packing:

Available in 25Kg bag.

Handling Precautions:

Classic Crete TA is non-toxic. However, splashes on the skin should be washed well with water and if contact with eye occurs, wash well with water and seek medical advice.

Variety of Products:

Following are the other similar products from Primadonn Buildtech Pvt. Ltd.

- Classic Coat-RB
- Classic Crackmate
- Classic Cure-C
- Classic Epoxy Mortar-301
- Classic Epoxy Patch-302
- Classic Epoxy Primer-273
- Classic Epoxybond-208
- Classic Epoxyseal-204
- Classic ETP-3
- Classic MA
- Classic Micromate
- Classic Primecoat
- Classic Repmate
- Classic Rust Shield
- Classic Strongcoat-202AR
- Classic TP
- Classic TT
- Classic Wall Putty

Primadonn Buildtech Pvt. Ltd.

(An ISO 9001:2015 Certified Company)

No: 349, RS Road, Srinivasa Nagar, Kavaraipettai, Gummidipoondi, Chennai-601206.

Phone: +91-9514709240

Mail: support@primadonn.com

www.primadonn.com