



CLASSIC CRETETM TT

High Performance Single Component Tile on the Adhesive

Description:

Classic Crete TT has good flexibility and also can resist thermal movement. It can be used for external cladding of tiles and granite stones. It has good bonding even on smooth surface with excellent waterproofing properties.

Uses:

Classic Crete TT is a high quality adhesive single component for the permanent fixing of tiles, stones and granite including tile on tile. It can also be used for fixing of insulation and acoustic boards. Tiled surfaces after curing can be used for damp and submerged services like toilets and swimming pools.

Pack

Available in 5 & 25 Kg bags.

Instruction for Use:

Surface Preparation:

AA surfaces must be sound and thoroughly cleaned before **Classic Crete TT** is applied. All traces of grease or oil must be removed with suitable degreaser. All loose particles of mortar and paints must be physically removed.

Mixing:

Mixing 3 to 3.5 parts of **Classic Crete TT** into a part of potable water by volume and mix into a creamy consistency. Water can be reduced or increased slightly to achieve required consistency. A slow speed drill fitted with a suitable mixing paddle is recommended. Hand mixing may also be restored if drill/paddle is not

available. Powder to be added slowly to the water and not water to powder.

Application:

Classic Crete TT can be applied directly on concrete, cement screeds, cement lime mortar and tiles. It can bond well even on smooth surface.

Finishing:

Remove excess adhesive with a damp cloth before material has set. Joint grouting may be commenced 24 hours after tiles have been laid, with **Classic Crete TP** joint filler.



CLASSIC CRETETM TT

High Performance Single Component Tile on the Adhesive

Coverage:

Classic Crete TT is spread behind the tile to a uniform thickness of 3 to 5 mm. It covers approximately 5 Sq.mt. at a thickness of 3 mm per 25 Kg pack.

Handling Precautions:

Classic Crete TT is non-toxic. However, splashes on the skin, should be washed well with water and if contact with eye occurs wash well with water and seek medical advice.

Variety of Products:

Following are the other similar products from Primadonn Buildtech Pvt Ltd.,

- Classic Coat-RB
- Classic Crackmate
- Classic Cure-C
- Classic Epoxy Mortar-301
- Classic Epoxy Patch-302
- Classic Epoxy Primer-273
- Classic Epoxybond-208
- Classic Epoxyseal-204
- Classic ETP-3
- Classic MA
- Classic Micromate
- Classic Primecoat
- Classic Repmate
- Classic Rust Shield
- Classic Strongcoat-202AR
- Classic TA
- Classic TP
- Classic Wall Putty

TAMILNADU

Corporate Office

PRIMADONN BUILD TECH PVT LTD

No. 349, First Floor, Srinivasa Nagar, Kavaripttai, Gummidipoondy 601 206.

Ph+91-8220513172,

Admin Office:

No.605, Selva Vinayaga Nagar, Grant Lyon Village, Ponneri Tk., Thiruvalluvar Dt., Ph+91-6379174327, +91-8438276059.

Manufacturing Unit

No.603, Selva Vinayaga Nagar, Grant Lyon, Vadagarai, Chennai 600 052. Ph.+91-9444907177

KARNATAKA

Corporate Office:

PRIMADONN CONSTRUCTION CHEMICALS (P) LTD.,

Talacauvery Layout, Basavanagar, Bangalore 560 037. Ph.+9150878429, +91-9345411355.

PONDICHERRY

Branch Office

192/A, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-4208833, 91-+9514709240

Distributor's

151, Chinna Subburaya Pillai Street, Near Vaikal Cutting, Puducherry 605 001. Ph.0413-2222100, 91-+9345561820

Email: Info@Primadonn.com, www.Primadonn.com

